



NLS Inflow Pressure Screen

Application&Feature

1. Small motor power, high production capacity, energy saving.
2. Inflow structure, low pulse, good effect of homogenate.
3. No gaskets companion flange pulp outlet, inwall is polished. Seamless connection of flow pipeline, no fiber hitching.
4. Automatic oil injection device, seal water detection alarm device ensure the safe running of equipment and reduce maintenance.
5. Advanced structure, sturdy and durable, convenient disassembly and assembly, simple operation, less malfunctions for continuous working, low maintenance cost.

Main Specification

Type	NLS0.6	NLS1	NLS1.5	NLS2	NLS3	NLS4	NLS5	NLS6	NLS7	
Screen Area (m ²)	0.6	1	1.5	2	3	4	5	6	7	
Concentration Of Input Pulp(%)	0.4-0.8									
Production Capacity (t/d)	Screen Hole(t/d)	30-60	70-130	110-160	140-260	250-400	260-520	350-600	420-700	500-900
	Screen Slot(t/d)	25-45	55-80	80-120	100-160	150-300	180-320	220-400	260-480	350-600
Pressure Of Inflow Pulp(mpa)	0.1-0.4									
Motor Power (kw)	7.5-15	22	30	37	45	55	75	90	110	